



**Innovative Solutions
for Water, Air & Energy**



[evansproducts.com](https://www.evansproducts.com)

COMPANY PROFILE



Presence in
25 Countries

INNOVATING SOLUTIONS to improve your quality of life in vital aspects such as **WATER, AIR AND ENERGY** through products that facilitate your activities at home, work and industry.



800
Employees

FOR MORE THAN 40 YEARS our main objective has been to focus on the design, engineering and development of our equipment, and generate growth with new durable and reliable products that exceed our customer's expectations.



30 ACRES
for design, manufacturing
and storage

EVANS® is based on El Salto Jalisco Mexico within an industrial park that covers over 30 acres.

The complex has cutting-edge technology for manufacturing processes that include modeling, laser cutting, machining, stamping, welding, electrostatic painting and more which together produce 2 million pieces per year.

With constant growth, today we are one of the three most important factories of Lawn Mowers worldwide. We are also leaders in other categories as generators, air compressors, water pumps, pressure washers and solar energy.





We have established alliances around the world with premium engine manufacturers to power our diesel, gas and gasoline products.

VOLVO
PENTA

VANGUARD



SCANIA

Kubota



Since our products are specialized we have trained our team to provide technical and commercial advice within our Evans brand stores and franchised stores. Also provide designed of exhibition and demonstration spaces that help the customer to get involved with the products and understand better the advantages.

"OUR MISSION IS TO PROVIDE SOLUTIONS THAT CAN HELP YOUR BUSINESS GROW"

To be able to supply and help all customer segments we have different distribution channels, business models, strategies and commercial support that adapt to each of our consumers.



2 MILLION
Pieces produced every year



10 Fullfilment
Centers



3,000
Different products



POULANPRO



MULTIPLE CUTTING MODES

Switch easily from bagging, mulching or side discharge.



HIGH REAR WHEELS

For extra maneuverability on all terrains.



VARIABLE SPEED

The bottom bail can be used to easily set your personal pace.



ADJUSTABLE CUTTING HEIGHT

Choose from different height positions based on your lawn condition.



UP TO 30% LESS PULLING EFFORT



2 PULL GUARANTEED START

BRIGGS & STRATTON'S READY START SYSTEM™ GUARANTEES A START IN UNDER TWO PULLS

POWERED BY:



12" WHEELS

EASIER HANDLING WHILE GETTING THE JOB DONE



9 POINTS

HEIGHT ADJUSTMENT



22" HIGH LIFT BLADE



SELF PROPELLED

FRONT WHEEL DRIVE EASES THE TASK

MANUFACTURED IN BY



POULANPRO®

- Poulan Pro lawn mowers are efficient, lightweight and hardworking.
- Multiple engine, drive systems and cutting deck choices.



MODEL	ENGINE MODEL	TORQUE	CUTTING WIDTH	DRIVE SYSTEM	FEATURES	HEIGHT ADJUSTMENT	HEIGHT RANGE	WHEELS
PM20N450S	450E	4.5 lb-ft	20"	Push	Cut only	Five Points	1.25"-3.44"	7/7"
PM21N550SH	550E	5.5 lb-ft	21"	Push	Cut/Mulch	Five Points	1.25"-3.28"	8/11"
PM21N550R	550E	5.5 lb-ft	21"	Push	Cut/ Mulch/ Bag	Five Points	1.25"-3.28"	8/8"
PM21N550RH	550EX	5.5 lb-ft	21"	Push		Five Points	1.25"-3.28"	8/11"
PM21N625RH	625EX	6.25 lb-ft	21"	Push		Five Points	1.25"-3.28"	8/11"
PM22Y625RH	625EX	6.25 lb-ft	22"	FWD		Nine Points	1.25"-3.45"	8/12"
PM22Y675RH	675EX	6.75 lb-ft	22"	FWD		Nine Points	1.25"-3.45"	8/12"



• Immediate home power during outages and natural disasters.



		GER10LP2300BS	GER17LP3500BS
PRIME POWER (PRP)	EMERGENCY STANBY POWER (ESP)	12 kVA	16.6 kVA
	PRIME POWER (PRP)	10 kVA	15 kVA
	POWER FACTOR	1	
	VOLTAGE SYSTEM	240/120VAC	
	PHASES	Single phase	
	FREQUENCY	60 HZ	
	DIGITAL CONTROLLER	SMARTGEN® HGM420N	
	ENCLOSURE TYPE	Sound proof cabin	
	HOUSING PROTECTION	IP23	
	NOISE LEVEL @7M	72 dB(A)	
ENGINE	ENGINE BRAND	VANGUARD®	
	MODEL	BS-LP230G	BS-LP340G
	ENGINE TYPE	V-TWIN, OHV	
	RATED POWER	23 HP	35 HP
	ENGINE SPEED	3600 RPM	
	FUEL	Propane / Natural Gas	
	DISPLACEMENT	627 cc	993 cc
	FUEL CONSUMPTION	0.45 L/kWh	
	OIL CAPACITY	1.7 L	2.3 L
	COOLING SYSTEM	Forced air cooling	
ALTERNATOR	BATTERY	12 VDC 20AH sealed AGM type	
	BRAND	NSM®	
	MODEL	M100LL	M112SD
	TYPE	Brushless	
	ELECTRIC CONNECTION	4 pin serial	
	INSULATION TYPE	H	
	BREAKER CAPACITY	50 A	63 A
ATS	CABLE GAUGE PER PHASE	10 AWG	10 AWG HIGH TEMP
	TYPE	Mechanical and automatic	
	RATED CURRENT	63 A	125 A



VANGUARD

Please refer to warranty statement.



PORTABLE GENERATORS



- Continuous power for heavy duty construction and natural disaster emergencies.
- Robust and portable.
- Easy to transport.
- Extremely fuel efficient engines.



VANGUARD

Please refer to warranty statement.



	G40MG0650V	G50MG1000V	G80MG1400V	G80MG1400VAE	G110MG1800VAE	G135MG2300VAE	G185MG3500VAE	
ENGINE	ENGINE BRAND VANGUARD®							
	ENGINE POWER	65HP@3600RPM	10HP@3600RPM	14 HP @ 3 600 RPM		18HP@3600RPM	23HP@3600RPM	35HP@3600RPM
	DISPLACEMENT	230 cc	305 cc	408 cc		570 cc	627 cc	993 cc
	START TYPE	Recoil			Electric /Recoil			
	ENGINE TYPE	Air cooled, four strokes one cylinder ohv gasoline engine				Air cooled, four strokes two cylinder ohv gasoline engine		
	FUEL TANK CAPACITY	15 L (4 gal)	25 L (6.6 gal)			30 L (9.25 gal)		45 L (12 gal)
CARACTERÍSTICAS	OPERATING TYPE AT 50% LOAD	10 hr	12 hr	11 hr		7.3 hr	6.3 hr	7 hr
	MAX. POWER	3.5 kVA	5 kVA	8 kVA		11 kVA	13.5 kVA	18.5 kVA
	PRIME POWER	3.4 kVA	4.5 kVA	6.5 kVA		9.5 kVA	12 kVA	17 kVA
	VOLTAGE	115 VAC ~		115 / 230 VAC ~			115 / 230 V	
	COOLING TYPE	Air Cooled						
	NOISE LEVEL @ 7 M	74 dB	75 dB	77 dB		70 dB	88 dB	85 dB
	DISPLAY ARRAY	1 Duplex receptacle 115 VAC 5-20R + OPS (Overload protection)	2 duplex receptacles 115 VAC, 1 receptacle twist lock 230/115 VAC L14-30R + OPS ,Voltmeter, 115 VAC max power switch				2 duplex receptacles 115V 2 Twist Lock 240 V 115 VAC overload protection + breaker	3 duplex receptacles 115V 3 Twist Lock 240/120 VAC overload protection + breaker



WELDER / GENERATOR



- Professional welder generator, driven by a 23 HP VANGUARD® gasoline engine.
- Designed in a compact lightweight cabin that can be transported in any truck bed.
- Low fuel consumption.
- Powerful backup Generator and continues welding power.



VANGUARD

Please refer to warranty statement.



W350MG2300BS

RECOMMENDED ELECTRODES TYPES AND SIZES

ELECTRODE	Φ 3/32"	Φ 1/8"	Φ 5/32"	Φ 3/16"
E-6013	✓	✓	✓	✓
E-7018	✓	✓	✓	✓

		W350MG2300BS
WELDER	SERVICE	350A -35%, 300A-60%, 220A-100%
	HOUSING PROTECTION	IP23
	ELECTRODE TYPE	Basic cellulosic electrode (up to 1/4")
	ELECTRODE SIZE	3/32 - 3/16 pulg (up to 1/4 pulg)
	WELDING SELECTOR	24 positions
GENERATOR	DC WELDING RANGE	From 40 to 350 a cd
	PRIME POWER	8 KVA
ENGINE	PRIME VOLTAGE	230 V~ / 115 V~
	PRIME CURRENT	33 A / 66 A
	FREQUENCY	60 HZ
	ENGINE BRAND	VANGUARD®
	POWER	23 HP @ 3 600 RPM
	GAS TANK	45 L (11.6 gal)

WATER PUMPS



- Self-priming pumps: clear air from the suction hose, can start without water.
- Heavy duty option: pump made 100% from cast iron, including impeller, for an extra long service life.
- Ideal for water transfer applications in construction sites, farms, irrigation or emptying flooded areas.
- Equipped with Vanguard engines with Integrated Cyclonic Air Filtration that doubles your equipment's air filter replacement intervals to 600 hours.
- Three year limited warranty on the engine. One year on the pump end.



Suction hose and lay flat hose kit with quick fittings. (Sold separately)

VANGUARD **3** YEAR WARRANTY **+1** YEAR WARRANTY
Please refer to warranty statement.

MODEL	INLET	OUTLET	POWER	DISPLACEMENT	ENGINE	MAX HEAD	MAX FLOW	MAX EFFICIENCY	SOLID PASSAGE
AC2AMG0650V	2"	2"	6.5 HP	203 cc	VANGUARD®	108 ft	146 gpm	92 gpm @ 50 ft	1/4"
AC3AMG0650V	3"	3"				85 ft	277 gpm	142 gpm @ 52 ft	
AC2MG0650V	2"	2"				99 ft	182 gpm	118 gpm @ 50 ft	3/4"
AC3MG0650V	3"	3"				85 ft	262 gpm	157 gpm @ 52 ft	1"
AC4MG1000V	4"	4"				10 HP	305 cc	70 ft	422 gpm

DUE TO CONSTANT PRODUCT IMPROVEMENT, THE PRODUCT MIGHT DIFFER SLIGHTLY FROM THE PICTURE.



33 ft HOSE

12 HOURS
USE PER DAY

1 YEAR WARRANTY

- Recommended for residential construction market, commercial shops, vehicle, farm and cattle cleaning, manufacturing facilities, oil wells, sewer systems or agricultural applications.
- Equipped with Vanguard engines with integrated cyclonic air filtration.
- Filtration that doubles your equipment's air filter replacement intervals to 600 hours and with its horizontal design it expands the engine lifetime.
- Three year warranty on the engine, 1 year warranty on the pump.



VANGUARD

Please refer to warranty statement.

3 YEAR
COMMERCIAL LIMITED WARRANTY

+1 YEAR
WARRANTY COMMERCIAL YEAR

MODEL	WATER FLOW	PRESSURE	ENGINE	MAX. WATER TEMP.	POWER	START	DISPLACEMENT	FUEL TANK CAPACITY
HC3G28MG0650V	12 lpm (3.3 GPM)	186 bar (2700 PSI)	VANGUARD®	60 °C	6.5 HP	Recoil	203 cc	3.1 L
HC4G30MG1000V	18 lpm (4 GPM)	206 bar (3000 PSI)			10 HP		305 cc	
HC6G40MG1400V	21 lpm (5.5 GPM)	275 bar (4000 PSI)			14 HP		408 cc	5.6 L
HC6G40MG1400VAE							Electric	



- Used by building and roof contractors, auto repair shops, paint shops.
- Heavy duty contractor pro use.
- Fits into tight spaces.
- Equipped with Vanguard engines with Integrated Cyclonic Air Filtration that doubles your equipment's air filter replacement intervals to 600 hours and with its horizontal design it expands the engine lifetime.
- Three year limited warranty on the engine. One year on the air compressor pump.



VANGUARD

Please refer to warranty statement.



MODEL	AIR DELIVERY		MAX. PRESSURE	CYLINDERS	TANK CAPACITY	NOISE LEVEL	POWER	DISPLACEMENT	FUEL TANK CAPACITY
	@40 PSI	@90 PSI							
E170MG0650V-010	12.5 SCFM	10.80 SCFM	8 bar (116 PSI)	2	10.6 gal (40L)	89 dB (A)	6.5 HP 3600 RPM	203 cc	3.1 L



CUSTOMER SERVICE

Phone: (866) • 260 • 4843

Whatsapp: (346) • 386 • 8830

sales@evansproducts.com

[evansproducts.com](https://www.evansproducts.com)



Evans USA



MADE IN MX